

## **DECLARATION OF PERFORMANCE**

according annex III of the regulation (EU) No. 305/2011 for the product

# WAKOL A 850 Filling Compound

No 400429549687200

1. Unique identification code of the product type:

### EN 13813 CA-C30-F7

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

#### Calcium sulphate based levelling compound for floors indoors

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR

### Wakol GmbH Bottenbacher Straße 31 D-66954 Pirmasens

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4 / System 3 fire resistance

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body **1378** carried out the determination of the product type on the basis of type testing and issued a: test report

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued:

not applicable

#### 9. Declared performance

| Essential characteristics       | Performance | Harmonized technical spezification |
|---------------------------------|-------------|------------------------------------|
| Reaction to fire class          | A1/A1fl     |                                    |
| Release of corrosive substances | CA          |                                    |
| Water permeability              | NPD         | EN 13813:2002                      |
| Water vapour permeability       | NPD         |                                    |
| pH value                        | ≥7          |                                    |
| Compressive strength            | C30         |                                    |
| Flexural strength               | F7          |                                    |
| Wear resistance                 | NPD         |                                    |
| Sound insulation                | NPD         |                                    |
| Tensile adhesions strength      | NPD         |                                    |
| Shock resistance                | NPD         |                                    |
| Sound absorbtion                | NPD         |                                    |
| Thermal resistance              | NPD         |                                    |
| Chemical resistance             | NPD         |                                    |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Martin Schot

Pirmasens, 01.07.2021

Dr. Martin Schäfer Director Research & Development, Technical Service and Purchasing

F31LDE, R02, 01/07/21

P:\TI-GUELTIG\TI Bau\Technische Zusatzinformationen Bau\Leistungserklärung\F75057 0100 WAKOL A 850

