

Relaxed levelling!



WAKOL D 3060 Plastification Additive

Versatile – expands the application range of the Wakol levelling compounds

Versatile – replaces numerous special products

Safe – improves adhesion and strain characteristics

State-of-the-art – best consumer protection according to EMICODE EC1 PLUS

Product:



WAKOL®
Anspruch verbindet

WAKOL D 3060 Plastification Additive – fitness for the levelling compound



Finishing with new possibilities

WAKOL D 3060 Plastification Additive is a ready-to-use dispersion and replaces mixing water for blending approved Wakol levelling compounds. The result is a significant improvement in adhesion to the subfloor, less strain from shrinkage, with increased elasticity of the levelling compound layer. Additional applications then become possible:

Directly levelling over old adhesive residue

In the past, a two-staged procedure was required for all waterproof adhesive residue – priming and then levelling. WAKOL D 3060 Plastification Additive combined with a suitable Wakol levelling compound makes the primer unnecessary, so that the surface can be directly levelled in a single operation.

Direct levelling of old, fixed existing floor coverings

Where time-intensive and labour-intensive removal of the floor covering was often necessary, with old needle fleece flooring, for example, WAKOL D 3060 Plastification Additive combined with a suitable Wakol levelling compound now allows direct levelling of the old covering. In addition, cleaned CV, PVC & ceramic tile surfaces can be directly levelled. A plasticiser block can also be achieved in existing floor coverings containing plasticisers, in order to rule out plasticiser interactions in the subsequent laying.

Levelling over screw holes and borders

WAKOL D 3060 Plastification Additive combined with a suitable Wakol levelling compound is much more economical when filling screw holes and borders in wooden material tiles compared with a dispersion-based levelling compound. Impact marks of trowels can also be filled in, for example.

Filling cable ducts and other transitional areas

WAKOL D 3060 Plastification Additive combined with a suitable Wakol levelling compound is ideally suited for filling in WAKOL AR 150 Reinforcement Fabric wherever different subfloors abut one another and there is a risk of tearing. Even metal wiring ducts otherwise requiring elaborate treatment can be directly filled previous priming.

Complete levelling of cork and rubber granule mats

WAKOL D 3060 Plastification Additive combined with a suitable Wakol levelling compound allows direct levelling of cork and rubber granule mats, such as WAKOL TS 102 Footfall Soundproofing Mat, 2mm without priming. Depending on the application, the applied layer serves

- as a plasticiser block
- to distribute the strain or
- to remove roughness and unevenness of the mat surface

Please always observe the technical information before processing.