

For a quiet walk!



WAKOL MS 262 Parquet Adhesive, firm-elastic with WAKOL TS 160 Footfall Soundproofing Mat / WAKOL TS 170 Footfall Soundproofing Sheet

Quiet – optimal footfall soundproofing

Fast – laying in a single operation

Comfortable – easy removal of adhesive residue

State of the art – best consumer safety, very low in emissions, according to EMICODE

Product:



WAKOL®
Anspruch verbindet

WAKOL MS 262 Parquet Adhesive, firm-elastic with WAKOL TS 160 Footfall Soundproofing Mat/ WAKOL TS 170 Footfall Soundproofing Sheet – footfall soundproofing quick and easy



Footfall soundproofing becomes easy

Requirements on footfall soundproofing are playing an increasingly important role particularly in multi-storey construction in combination with parquet flooring. WAKOL MS 262 Parquet Adhesive, firm-elastic in combination with WAKOL TS 160 Footfall Soundproofing Mat or WAKOL TS 170 Footfall Soundproofing Sheet affords optimal footfall soundproofing for multilayer and solid parquet with matchboard joining in the simplest laying technology. What seems complicated becomes simple and fast as well.

WAKOL MS 262 Parquet Adhesive, firm-elastic

- The MS polymer adhesive in the sausage
- Simple, easy use
- Good resistance to scoring
- Adhesive residue is easy to remove from sealed parquet surfaces
- Connected systems
- EMICODE EC1 PLUS

WAKOL TS 160 Footfall Soundproofing Mat

- Slit polypropylene soundproofing mat, 3 mm
- Easy handling thanks to light weight of 120 g/m²
- Good flatness through aluminium lamination
- EMICODE EC1

WAKOL TS 170 Footfall Soundproofing Sheet

- Slit cork mat, 2,5 mm
- Easy handling thanks to handy size and light weight of 475 g/m²
- Good flatness
- EMICODE EC1 PLUS

Laying in a single operation

Simply unroll WAKOL TS 160 Footfall Soundproofing Mat loose respectively lay out WAKOL TS 170 Footfall Soundproofing Sheet joint to joint. Then introduce WAKOL MS 262 Parquet Adhesive, firm-elastic



with commercially available sausage gun or battery-operated WAKOL Applicator 50 in the slits provided in the WAKOL TS 160 Footfall Soundproofing Mat / WAKOL TS 170 Footfall Soundproofing Sheet. Lay parquet on top. Finished!

Footfall soundproofing for the highest requirements

10 mm multi-layer parquet laid with WAKOL MS 262 Parquet Adhesive, firm-elastic on WAKOL TS 160 Footfall Soundproofing Mat already improves footfall soundproofing by a factor of 17 dB according to EN ISO 140/8. On 14 mm multi-layer parquet WAKOL TS 170 Footfall Soundproofing Sheet improves footfall soundproofing by a factor of 15 dB according to EN ISO 140/8. The firm connection to the subfloor also greatly reduces room sound.

Advanced protection of processor and consumer

WAKOL MS 262 Parquet Adhesive, firm-elastic on WAKOL TS 160 Footfall Soundproofing Mat / WAKOL TS 170 Footfall Soundproofing Sheet is a unique footfall soundproofing system. And this along with all the advantages of state-of-the-art MS technology, such as easy removability of parquet surfaces by hand. Both systems are approved* by the German Institute of Building Technology (DIBt) and are very low in emissions according to EMICODE.

Please always observe the technical information before processing.

* approval for WAKOL TS 170 Footfall Soundproofing Sheet pending

