

Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL PU 272 Artificial Turf Adhesive A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com +49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

(Contd. on page 2)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive
- · Dangerous components:

CAS: 67-64-1 acetone >1-≤2.5%

Reg.nr.: 01-2119471330-49 EUH066

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 2)

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

· DNELs

67-64-1 acetone

Oral DNEL 62 mg/kg/day (general population (long-term))

Dermal DNEL 62 mg/kg/day (general population (long-term))

186 mg/kg/day (workwr (long-term))

Inhalative DNEL 200 mg/m³ (general population (long-term))

2,420 mg/m³ (workers (short-term))

1,210 mg/m³ (workwr (long-term))

· PNECs

67-64-1 acetone

PNEC 10.6 mg/l (freshwater)

1.06 mg/l (sea water)

21 mg/l (water - partially release)

(Contd. on page 4)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 3)

100 mg/l (STP)

PNEC 29.5 mg/kg (soil)

3.04 mg/kg (sediment (sea water))

30.4 mg/kg (sediment (freshwater))

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

If the occupational exposure limit is exceeded.

- · Recommended filter device for short term use: Combination filter A-P2
- · Hand protection



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Fluid · Colour: Beige

Smell: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

421 °C

(Contd. on page 5)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 4)

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

• Flash point: 44 °C (DIN EN ISO 3679)

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· kinematic (calculated) at 40°C:

- dynamic at 20 °C: 180,000 mPas (ISO 2555)

· Solubility

· Water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Steam pressure: Not determined.

· Density and/or relative density

• **Density at 20 °C** 1.85 g/cm³ (EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form:

Important information on protection of health and

environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

• Organic solvents: 2.0 %
 • VOC 2.0 %

• **Solids content:** 98.0 % (DIN EN 827.8.2)

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void

(Contd. on page 6)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Void

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

· Desensitised explosives

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat) (OECD RL 401)

Dermal LD50 >15,800 mg/kg (rat)

Inhalative LC50/4h 76 mg/l (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

67-64-1 acetone

NOEC/16h 1,700 mg/l (Pseudomonas putida)

NOEC/48h 4,740 mg/l (Selenastrum capricornutum)

LC50/96h 11,300 mg/l (Leuciscus idus) (DIN 38412 T.15)

5,540 mg/l (Oncorhynchus mykiss)

8,300 mg/l (Lepomis macrochirus)

LC50/48h 12,600 mg/l (Daphnia magna)

11,300 mg/l (Leuciscus idus)

(Contd. on page 7)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 6)

EC5/16h 1,700 mg/l (Pseudomonas putida) EC5/72h 28 mg/l (Entosiphon sulcatum) EC5/8d 530 mg/l (Microcystis aerruginosa) EC50/18h 12,600–12,700 mg/l (Daphnia magna)

EC50/48h 6,100 mg/l (Daphnia magna)

EC50/96h 8,300 mg/l (Lepomis macrochirus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG · IATA Void UN1133

· 14.2 UN proper shipping name

· ADR, ADN, IMDG Void

· IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG

· Class Void

· IATA



· Class 3 Flammable liquids.

(Contd. on page 8)



Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

3

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 7)

·Label

· 14.4 Packing group

· ADR, IMDG Void
· IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

 \cdot ADR

• Remarks: Is not subject to the regulations of ADR for packings up

to 450 l (see ADR 2.2.3.1.5)

 \cdot *IMDG*

• Remarks: Is not subject to the regulations for placards, labeling

and examination after the IMDG code for packings up to

30 l

Void

transport in accordance with IMDG Code 2.3.2.5

· UN "Model Regulation":

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · National regulations
- · **VOC (EU)** 37.0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)





Printing date 09.11.2022 Version number 11 (replaces version 10) Revision: 09.11.2022

Trade name: WAKOL PU 272 Artificial Turf Adhesive A

(Contd. of page 8)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids — Category 3
Eye Irrit. 2: Serious eye damage/eye irritation — Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Revision: 23.03.2023



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2023

Version number 11 (replaces version 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL PU 272 Artificial Turf Adhesive B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com

+49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2 H319 Causes serious eve irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 1)

Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe mist/vapours/spray.P280 Wear protective gloves / eye protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive
- Dangerous components:

CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

>50-<u><</u>100%

EC number: 618-498-9 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. (Contd. on page 3)

- GB



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 3)

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

· DNELs

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

Dermal DNEL 27.8 mg/kg/day (workers (Short-term))

DNEL 17.2 mg/cm² (general population (short-term))

Inhalative DNEL 0.05 mg/m³ (general population (short-term))

0.025 mg/m³ (general population (long-term))

0.1 mg/m³ (workers (Short-term))

0.05 mg/m³ (workers (Long-term))

· PNECs

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

PNEC 1 mg/l (Freshwater)

0.1 mg/l (Sea water)

10 mg/l (Water - partially release)

1 mg/l (Purification plant)

PNEC 1 mg/kg (Soil)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Combination filter A-P2
- · Hand protection



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

(Contd. on page 5)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 4)

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

10 °C

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Smell:
Odour threshold:
Fluid
Green
Characteristic
Not determined.

· Melting point/freezing point:

· Boiling point or initial boiling point and boiling

range 201 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: >200 °C
 Auto-ignition temperature: >600 °C
 Decomposition temperature: Not determined.

· pH at 20 °C

· Viscosity:

· Kinematic viscosity Not determined.

· kinematic (calculated) at 40°C:

- dynamic at 20 °C: 90 mPas (ISO 2555)

·Solubility

· Water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Steam pressure at 20 °C: <0.00001 hPa

Density and/or relative density

• **Density at 20 °C** 1.23 g/cm³ (EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 6)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 5)

Important information on protection of health and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

• Organic solvents: 0.0 % • VOC 0.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids Void · Self-heating substances and mixtures · Substances and mixtures, which emit flammable Void gases in contact with water Void · Oxidising liquids · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

Oral LD50 > 10,000 mg/kg (Rat) (OECD RL 401)

Dermal LD50 >9,400 mg/kg (rabbit) (OECD RL 402)

· Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 7)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 6)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

LC50/96h >1,000 mg/l (Danio rerio)

LC0/96h >1,000 mg/l (Brachydanio rerio)

EC50/24h >100 mg/l (bacteriums)

EC50/48h >1,000 mg/l (Daphnia magna)

EC50/3h >100 mg/l (sludge) (OECD 209)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

(Contd. on page 8)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 7)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · GEV-Guidline/EMICODE:

EC 1 plus R, "very low emission"

(as ready-for-use mixture with component A)

- · VOC (EU) 0.4 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 9)



Printing date 11.12.2023 Version number 11 (replaces version 10) Revision: 23.03.2023

Trade name: WAKOL PU 272 Artificial Turf Adhesive B

(Contd. of page 8)

EUH204 Contains isocyanates. May produce an allergic reaction.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2