

WAKOL L 1940 Spray Adhesive

Technical Information

Area of application

Solvent-based, sprayable contact adhesive for laying coverings on stairs of

- textile flooring such as tufting, web and needle fleece flooring
- Linoleum flooring
- rubber flooring
- Plasticizer-free skirting boards

on properly prepared absorbent and non-absorbent subfloors indoors.

Special properties

- Very short airing time
- long open time

Technical data

Raw material base:	Synthetic rubber
Application method:	Spray a thin layer on both sides
Airing time:	1-2 minutes
Laying time	4 hours
Setting time:	approx. 24 - 48 hours
Temperature resistance:	up to 110 °C (temporarily)
Cleaning agent:	WAKOL RV 105 Neoprene Dilution
Storage time:	12 months in the sealed container
Storage temperature:	protect against direct sunlight, not below +5 °C and not over +50 °C

Application and consumption¹⁾

Spray nozzle	160-180 ml/m ² with application on both sides	Textile flooring Linoleum flooring Rubber flooring Plasticizer-free skirting boards
--------------	--	--

1) Consumption is dependent on surface structure and absorbability of subfloor.

Subfloors

The subfloor as well as the room climate conditions must meet the requirements of the applicable standards and data sheets. Subfloors must be permanently dry, solid, level, free from cracks, dirt and adhesion-inhibiting substances.

Apply appropriate Wakol levelling compounds to uneven subfloors and mastic asphalt. The technical information on the primers and levelling compounds must be heeded.

Usage

Spray adhesive evenly onto covering and subfloor at a distance of approx. 5-8 cm from spray nozzle. The spray intensity and direction can be adjusted via the nozzle.

Lay covering properly after airing is complete (finger test) and press on firmly. Then press on firmly/roll out with rubber hammer or pressure roller. Subsequent corrections are not possible.

Important

Processing not below floor temperature of +15 °C and room temperature of +18 °C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %. All information is based on approx. 20 °C and 50 % relative air humidity. In cold weather, warm up all laying materials in a heated room before use.

Do not use adhesive for materials containing plasticizer such as PVC/CV coverings.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the current national standards must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 10.12.2024 supersedes all previous versions.