

WAKOL R 4515 Tile Cleaner

Technical Information

Area of application

Cleaner for manual or machine application on old tiled floors for removal of layers of old care products and extreme dirt before subsequent tile laying.

Special properties

Technical data



1) Basic cleaner, irritant, containing solvents with skin-absorptive substances

Anionic and non-ionic surfactants
1:3
approx. 1 Litre WAKOL R 4515 Tile Cleaner / 20 m²
10.2
not below +5 °C, sensitive to frost
36 months in the sealed container
see safety data sheet

Usage

Dilute the WAKOL R 4515 Tile Cleaner with water at a ratio of 1:3. Spread the cleaner on the floor using a single-disc machine and a black pad, finishing the edges manually. Leave the WAKOL R 4515 Tile Cleaner to work for at least 10 minutes and then treat the surface again using a black pad or cleaning brushes. Then soak up the cleaning fluid, e.g. with a wet-suction device; do not allow to dry. Neutralise residues by cleaning again twice with clean water and allow the surface to dry before carrying out further work.

Important

Processing not below floor temperature of +15 $^{\circ}$ C and room temperature of +18 $^{\circ}$ C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %. All information is based on approx. 20 $^{\circ}$ C and 50 % relative air humidity.

Warm up all laying materials in due time in heated room.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the current national standards must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 07.09.2023 supersedes all previous versions.

451501GB02 0923 WAKOL R 4515 Tile Cleaner

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at Wakol Adhesa AG Schützengasse 28 CH-9410 Heiden Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl A Via Kennedy 75 I-20010 Marcallo con Casone Tel. +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp.z o.o. ul. Sławęcińska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel. +48 22 436 24 20 Fax +48 22 436 24 21 www.loba-wakol.pl Lecol Chemie B.V. Schutweg 6 NL-5145 NP Waalwijk Tel. +31 416 566 540 Fax +31 416 566 531 www.lecol.nl

Seite 2 von 2