

WAKOL RS 5950 Screed Edging Strips, 100 mm

Technical Information

Area of application

Permanently elastic screed edge strips made from polyethylene with adhesive strips for

- screed work
- WAKOL Z 560 Rapid Screed
- WAKOL Z 590 Light Screed
- Screeds from WAKOL EP 219 Screed Binder with WAKOL S 25 Elongating Sand indoors.

Technical data

Material:	8 mm thick, 100 mm high, PE insulation strips
Delivery:	Rolls, each 15 m / 5 rolls in a box
Storage time:	12 months at room temperature
Storage temperature:	store in a cool location not sensitive to frost
GISCODE:	not applicable

Usage

Screed insulation strip, which is secured to the wall using adhesive strips. Also tack the screed strips in the corners and if there is tension.

Important

Do not apply adhesive to finished surfaces.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the current national standards must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 26.06.2024 supersedes all previous versions.

Wakol GmbH
Bottenbacher Straße 30
D-66954
Pirmasens
Tel. +49 6331 8001 131
Fax +49 6331 8001 890
www.wakol.com



Wakol GmbH
Industriestraße 5
A-6841
Mäder
Tel. +43 5523 64 700
Fax +43 5523 64 700 64
www.wakol.at

Wakol Adhesa AG
Schützengasse 28
CH-9410
Heiden
Tel. +41 31 9210 755
Fax +41 31 9212 968
www.wakoladhesa.ch

Wakol Foreco srl
A Via Kennedy 75
I-20010
Marcallo con Casone
Tel. +39 02 9761 939
Fax +39 02 97 253 021
www.wakolforeco.it

Loba-Wakol Polska Sp.z o.o.
ul. Sławęcińska 16, Macierzysz
PL-05-850
Ożarów Mazowiecki
Tel. +48 22 436 24 20
Fax +48 22 436 24 21
www.loba-wakol.pl

Lecol Chemie B.V.
Schutweg 6
NL-5145 NP
Waalwijk
Tel. +31 416 566 540
Fax +31 416 566 531
www.lecol.nl