

WAKOL AS 130 Seaming Tape

Technical Information

Area of application

Polyester fleece tape for bonding seams in artificial lawns in indoor and outdoor area.

Special properties

- non-ageing
- low height
- heavy-duty
- waterproof

Technical data

Raw material base:	Polyester fleece with polyethylene coating
Dimensions:	100 m long, 30 cm wide
Weight:	135 g/m ²
Thickness:	0,39 mm
Maximum tensile force	280 N/50mm lengthways, 240 N/50 mm crosswise
Storage temperature:	not sensitive to frost

Subfloors

The subfloor must satisfy the requirements of the applicable standards and data sheets. Subfloors must be solid, level, free from cracks, dirt and adhesion-inhibiting substances.

Usage

Adequately acclimatise flooring before joining work. Prepare application machine with WAKOL AS 130 Seaming Tape and WAKOL PU 272 Adesivo para relva artificial. Secure seam tape at edge of playing field and move application machine in the seam as far as the opposite edge of the playing field. The sealing tape is placed under the flooring with adhesive, depending on the application machine check the seams and observe technical data of the adhesive.

Important

Processing not below floor temperature of +5 °C as well as humidity preferably between 40% and 65%, maximum 80%.

Warm up all laying materials in due time in heated room.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 12.09.2022 supersedes all previous versions.